

## Features:

- · Large, 3.25" (8.3 cm) universal icon and English display
- · Single-speed pressure pump with external (closed-loop) circulation capability
- LidDock™, DuraTop™
- · User-adjustable high and low temperature limits and alarms
- Single-point calibration
- · Complies with DIN 12876-1 Class I safety requirements for use with non-flammable liquids



Visual alarms alert you when bath temperature falls outside your pre-set limits.



Easy-to-use calibration function makes it simple to adjust the temperature display to match that of a traceable temperature standard.

For additional information on the MX Controller's features and capabilities, see pages 26 and 27.







7-Liter: +135°C

15-Liter: +135°C

20-Liter: +135°C

Temperature Range: Ambient +10° to +135°C

Working Access (L x W x D): 6.18 x 5.59 x 5" 15.7 x 14.2 x 12.7 cm

Overall Dimensions (L x W x H): 19.6 x 8.7 x 17.2" 49.9 x 22.1 x 43.7 cm

Temperature Range: Ambient +10° to +135°C

Working Access (L x W x D): 8.35 x 10.88 x 5.5" 21.2 x 27.6 x 14 cm

Overall Dimensions (L x W x H): 22.4 x 14.5 x 17.8" 56.9 x 36.8 x 45.2 cm

Temperature Range: Ambient +10° to +135°C

Working Access (L x W x D): 9.85 x 12.45 x 5.5" 25 x 31.6 x 14 cm

Overall Dimensions (L x W x H): 24 x 16.5 x 17.8" 61 x 41.9 x 45.2 cm

		I	I
Reservoir Size	7 Liter	15 Liter	20 Liter
Temperature Range	Ambient +10° to +135°C		
Heater	1100 W		
Part Number 120 VAC/60 Hz	MX07H135-A11B	MX15H135-A11B	MX20H135-A11B
Part Number 240 VAC/50 Hz	MX07H135-A12E	MX15H135-A12E	MX20H135-A12E

Electrical plugs for the part numbers listed are standard U.S. and European types. See page 128 for additional plug types and part numbers.