

MATERIAL SAFETY DATA SHEET

Section I – Product Information								
Product Name or Identity:	Fluid Thioglycollate Medium							
Manufacturer's Name:	Acumedia Manufacturers, Inc. Emergency Phone No. 517/372-9200							
	740 East Shiawassee Fax No.: 517/372-2006							
Lansing, Michigan 48912 e-mail: foodsafety@neogen.com								
Date Prepared or Revised: 10/10/04								

Section II – Hazardous Ingredients / Identity Information					
Hazardous Components: (Specific Chemical Identity: Common Names)	OSHA PEL (Permissible Exposure Limits)	ACGIH TLV (Threshold Limit Value)	Toxicity Data LD ₅₀		
Sodium Chloride, NaCl, Common salt	N/A	N/A	ORL-RAT, 3000 mg/kg		
Sodium Thioglycollate	N/A	N/A	ORL-MSE, 504 mg/kg		

Section III – Physical Characteristics				
Boiling Point: 1413°C (Sodium Chloride)	Specific Gravity (H ₂ O = 1): 2.16 g/cm ³ (Sodium Chloride)			
Vapor Pressure (mm Hg.): 1.0 @ 865°C (Sodium Chloride)	Melting Point: 804°C (Sodium Chloride)			
	300°C (Sodium Thioglycollate)			
Vapor Density (AIR = 1): N/A	Evaporation Rate (Butyl Acetate = 1): N/A			
Solubility in Water: 35.7 g/100g at 0°C (Sodium Chloride), Soluble at 20°C (Sodium Thioglycollate)				
Appearance and Odor: Colorless crystals or white powder. Characteristic odor. (Sodium Chloride).				
Powder, faintly beige (Sodium Thioglycollate)				

Section IV – Fire and Explosion Hazard Data				
Flash Point (Method Used): Not applicable Flammable Limits: LEL (Lower Explosive Limit) - N/A				
UEL (Upper Explosive Limit) - N/A				
Extinguishing Media: Suitable extinguishing agents. CO ₂ , extinguishing powder, or water spray				
Special Fire Fighting Procedures: Fight larger fires with water or alcohol resistant foam. Firefighters should wear protective equipment and self-contained breathing apparatus.				
;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;				

Unusual Fire and Explosion Hazards: During heating or in case of fire, poisonous gases are produced.

Section V – I	Section V – Reactivity Data												
Stability:	Unstable			ons to copic. Pr				ordinary	conditic	ns of	use	and	storage.
	Stable	Х											
Incompatibil	Incompatibility (Materials to Avoid): Reacts with acids, alkalis, bases, oxidizing agents, Lithium, and Bromine trifluoride.												
	Hazardous Decomposition or Byproducts: Phosphorous oxides, Sodium oxides, Carbon monoxide, Carbon dioxide, and Sulfur oxides. When heated to above 801°C it emits toxic fumes of chloride and sodium oxide.						n dioxide,						
Hazardous Polymerizati	May Occ on:	cur		Condition incompa			Dust ge	eneration,	exposure	to ai	r, exc	ess h	neat, and
	Will Not	Occur	Х										

Product # (s)_7137_

Section VI – Health Hazard Data						
Route(s) of Ent	ry: Inhalation? Yes	Skin? Yes	Ingestion? Yes			
Health Hazards: (Acute and Chronic)Harmful. Harmful if swallowed, inhaled, or absorbed through the skin. Irritating to eyes, respirator system, and skin.						
Carcinogenicit	 NTP? No (National Toxicology Program) 	IARC Monographs? No (International Agency for Research in Car	OSHA Regulated? No			
to respiratory tra	ct and mucous membranes.	kin and mucous membranes. Irritating e Exposure: If ingested, large doses ca				
brostration. Can produce delayed pulmonary edema. Effects may be delayed. Emergency / First Aid Procedures:						
	Eye Contact: Rinse opened eye for at least 15 minutes under running water. Seek medical attention. Skin Contact: Wash with plenty of soap and water for 15 minutes. Seek medical attention if irritation develops.					

Section VII – Precautions for Safe Handling and Use

Accidental Release Measures: Ventilate spill area. Wear suitable protective clothing. Wipe up with damp sponge or mop. Avoid inhalation, contact with eyes, skin, and clothing.

Waste Disposal Method: Dispose in accordance with all applicable federal, state, and local environmental regulations.

Handling and Storing: Keep container tightly closed. Protect from moisture and physical damage. Suitable for any general chemical storage area. Store away from oxidizing agents.

Other Precautions: Prevent formation of dust. Ensure good ventilation / exhaustion at the workplace. Avoid prolonged or repeated exposure.

Section VIII – Control Measures

Respiratory Protection (Specify Type): None required where adequate ventilation conditions exist. If airborne concentration is high, use an appropriate respirator or dust mask.

Ventilation:	Local Exhaust: 50 – 100 CFM	Special: N/A		
	Mechanical (General): N/A	Other: N/A		
Protective Gloves: Proper disposable gloves		Eye Protection: Chemical resistant safety goggles		

Other Protective Clothing or Equipment: Uniform, lab coat, or disposable lab wear.

Work / Hygienic Practices: Follow the usual precautionary measures for handling chemicals / powder. Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Avoid contact with eyes, skin, and clothing.

This document is believed to be correct, but does not purport to be all inclusive and shall be used only as a guide. Acumedia shall not be held liable for any damage resulting from handling or from contact with the above product. These suggestions should not be confused with state, municipal or insurance requirements, and constitute NO WARRANTY.